



BSC paints®

*Nayi Duniya
Naye Rang*

Industrial and
Decorative Paints





ABOUT US



BSC Paints, an ISO 9001:2015 certified company, is a foremost name among the leading manufacturers of Decorative Paints, Industrial Paints, Texture Paints, Cement Based products and its allied products.

BSC Paints has an excellent reputation in manufacturing products designed to meet the demanding standards of architectural and building industry professionals. Today, that reputation is the cornerstone of the company's continued success. Maintaining a heritage of commitment to quality and endless innovation, the company has been soaring new heights of success, with exclusive range of European and Japanese, textured and decorative paints.

The key to BSC paints' reputation is its solid commitment to excellence and quality, monitored through controlled testing in the laboratory and in the field. All products are backed by a technical team committed to maintaining product quality and constantly researching new or improved technologies to enhance product performance, application and safety.



CERTIFICATIONS

R & D CENTER In-House R&D Lab recognized by National Small Industries Corporation, New Delhi, Govt. of India

EXPORT HOUSE "Export House" recognition from Director General of Foreign Trade, Govt. of India

ISO 9001:2015: Quality Management System (QMS) certified by Eurocert Certifications (UK)

PAINT ASSOCIATIONS



Indian Paint & Coating Association



Indian Small Scale Paint Association





- ▶ Bsc Royal Luxury Emulsion
- ▶ Satty Premium Emulsion
- ▶ Patina Emulsion
- ▶ Eagle Emulsion
- ▶ Hisheen Luxury Emulsion
- ▶ Spark Int. Emulsion



- ▶ Ultimate Premium Plus Emulsion
- ▶ Ultra Advanced Weatherproof Emulsion
- ▶ Mava Premium Emulsion
- ▶ Magma Emulsion
- ▶ X- Guard Emulsion



- ▶ Panther Ext. Primer (WT)
- ▶ Micra Int. & Ext. Primer (WT)
- ▶ Tarang Int. Primer (WT)
- ▶ Amrella Red Oxide Metal Primer (ST)
- ▶ Amrella Pink Wood Primer (ST)
- ▶ Amrella Surfacer Primer (ST)
- ▶ Nc Putty Cement ▶ Wall Putty
- ▶ Acrylic Wall Putty ▶ BSC Level Plast



- ▶ Rustic
- ▶ Spray Coat
- ▶ Perlina
- ▶ Granules
- ▶ Dholpur
- ▶ Stone Finishes
- ▶ Stucco
- ▶ Superfine
- ▶ Multi Fancy
- ▶ Natural Stone
- ▶ Travintinno
- ▶ Sandy Matt
- ▶ Antique Gold
- ▶ Grain Hair



- ▶ Amrella Pre. Syn. Enamel
- ▶ Amrella Pre. Plus Syn. Enamel
- ▶ Amrella Lustre Finish Enamel
- ▶ Amrella Hammertone Enamel
- ▶ Amrella Furniture Enamel
- ▶ Amrella Industrial Enamel
- ▶ Sealer, Lacquer, Black Japan
- ▶ Clear Varnish



- ▶ PU Int. & Ext. Coating
- ▶ BSC Melamine Coating
- ▶ PU Int. Ext. Hardener
- ▶ BSC Wood Stain
- ▶ BSC NC Paint
- ▶ BSC QD Paint
- ▶ Epoxy Insulator
- ▶ Epoxy Zinc Phosphate Prime
- ▶ Epoxy Enamel
- ▶ TSA Enamel



- ▶ Bsc Pearl Gold, Silver, Copper
- ▶ Non Metallic
- ▶ Magic Coat
- ▶ Synthetic Spray Paints
- ▶ Sparkling Silicon Tc-100/
- ▶ Clear Coat/Top Coat(TC-200-TC500)



- ▶ Rain Guard (Water Repellent)
- ▶ Heat Resistant Coatings
- ▶ Flame Retardant Coating
- ▶ Stoving Enamel
- ▶ Glass lacquer Coating
- ▶ EVA Screen Ink



- ▶ RX 746
- ▶ 101 LWB+
- ▶ RX 776
- ▶ Concrete Hardener
- ▶ Damp Proof



- ▶ Water Base Thinner (acrylic Paint Diluter)
- ▶ Reducer (Synthetic Paint Diluter)
- ▶ Paint Remover ▶ NC Thinner
- ▶ Melamine Thinner ▶ PU Thinner
- ▶ Multi Purpose Thinner



- ▶ 4001 Distemper
- ▶ Delta Distemper



- ▶ Mild Grey
- ▶ Dark Grey
- ▶ Light Grey
- ▶ White Tone



BSC paints®



LOW VOC

eco friendly



Premium Luxury Interior Emulsion

BSC Royals Luxury is an exquisite emulsion paint that provides a luxurious finish and a silky glowing appearance to your walls. A water-based, 100% acrylic interior wall finish, it has excellent flow giving a near brush mark free finish. It offers high stain resistance. Walls painted with BSC Royals are easy to clean and maintain that new look for years. It also offers good anti-fungal properties, and can be applied on all types of smooth plasters, false ceilings, asbestos sheets, concrete etc.

(Also Available in Rb2, Rb7, Rb11, Rb22 Bases)

HISHEEN *rich look*

Luxury Interior & Exterior Emulsion

BSC Hisheen Rich Look Interior & Exterior Emulsion is a smooth water-based, modified acrylic, Interior & Exterior wall finish with silicon additives. BSC Hisheen Rich Look comes with a 5 years waterproofing and performance warranty. BSC Hisheen provides excellent resistance to growth of algae and fungi on the walls. This prevents appearance of black spots on walls due to algal growth. BSC Hisheen Rich Look provides extremely good protection against alkali and UV degradation thus ensuring that the shade doesn't fade for a long time and the paint lasts longer. BSC Hisheen gives an excellent glossy finish.

(Also Available in Rb2, Rb7, Rb11, Rb22 Bases)



SATTY Interior Premium Emulsion

BSC Satty Premium Emulsion provides a rich, soft and smooth finish to interior walls due to its super-acrylic quality. Its composition imparts excellent durability to the paint film. It is washable and most stains can be removed easily by sponging with a mild soap solution. It is also fungus and mildew resistant. It is available in wide range of contemporary and luxurious shades that lend rich premium aesthetics with superior flow and leveling. Satty can be applied on smooth plaster, false ceiling, asbestos sheets, concrete etc.

(Also Available in Bw1, Bw6, Bw22 Bases)





Patina

Interior Emulsion

Bsc Paints Patina Interior Emulsion is an acrylic emulsion paint that offers excellent smoothness to touch and an elegant, rich finish. A value for money emulsion it provides durable, smooth and rich finish to interiors. Bsc Paints Patina Interior Emulsion can be applied on smooth plasters, false ceiling, asbestos sheets, concrete etc.

(Also Available in Te1, Te6, Te22 Bases)



Interior Emulsion

Bsc Paints Eagle Interior Emulsion is a water thinnable interior wall coating which gives good performance. It is an ideal substitute for ordinary paints, meeting the protective & decorative needs of the interior surfaces of buildings.



INTERIOR COLLECTIONS



BSC paints®



ULTIMATE

Premium Exterior Emulsion

BSC Ultimate Contains high sheen that will make your walls sparkle. This adds elegance to your home and ensures that it makes heads turn and earn praises. It also contains UV resistant colour pigments to ensure cleaner and brighter shades. Ultimate advanced anti-algal bio pack prevents the formation of algae and keeps ugly black spots away. Ultimate introduce 7 year performance warranty that covers product performance against fading, flaking, peeling, algal growth and fungal growth as well. (Please refer to the BSC Ultimate product and warranty guide for more details)



ULTRA

Advanced Weather Proof Exterior Emulsion

BSC Ultra Advanced Anti Algal Weather Proof Emulsion is a water-based, modified acrylic, anti algal, high performance exterior wall finish. Its revolutionary formulation provides long-lasting exterior performance even in the most extreme tropical conditions of india. It's unique advanced anti algal chemistry ensures that exterior walls are provide with power-packed resistance against algae and fungi growth. It has very good dirt pick up resistance and dirt cleaning properties that give your exteriors a lasting beauty and extreme protection.



Mava

Premium Exterior Emulsion

Mava Premium Exterior Emulsion is a water-based is a water-based 100% acrylic, exterior wall finish. A high performance, long-lasting exterior paint specially formulated to with stand extreme tropical conditions of high rainfall, humidity and heat. Mava provides fresh looks to all exterior surfaces for years. In additions, Mava provides excellent protection against the growth of algae and fungus on the walls. It offers excellent protection against alkali and UV degradation too.





MAGMA

Exterior Acrylic Emulsion

Magma Exterior Acrylic Emulsion is a water-based exterior wall finish suitable for dry to moderate humid climatic conditions. It offers excellent resistance to chalking, cracking and weathering in comparison to Cement Paint. Magma gives cleaner shades which do not fade and last longer. Magma offers good anti-algal performance in dry to moderately humid climatic conditions.



X-GUARD™

Exterior Emulsion

BSC X-Guard Emulsion is a water thinnable exterior wall coating which gives good performance. It is an ideal substitute for ordinary paints, meeting the protective & decorative need of the exterior surfaces of buildings.



EXTERIOR COLLECTIONS



BSC paints[®]

PRIMER COLLECTIONS



MICRA

Cement Primer Exterior

BSC Micra Cement Primer is water based acrylic co-polymer Emulsion which can be applied over a variety of exterior walls, ceiling made of sand, cement plaster asbestos, cement brich, lime or pre-painted surfaces, POP etc. It offers smooth and matt finish, satisfies suction by sealing the surfaces, alkali and water resistance, excellent coverage, quick drying, good flow and leveling.



BSC paints
TARANG[™]

Cement Primer Interior

BSC Tarang Primer is a water-based wall primer that can be used on interior masonry surface. It has good whiteness, good coverage and flow and leveling properties. It is suitable for priming plastered walls, asbestos, cement, concrete etc.



AMRÈLLA[®] White Cement Primer (Synthetic)

BSC White primer is a solvent based undercoating that promises the perfect surface preparation for applying a white paint. Being manufactured from selected pigments it offers excellent topcoat holding property, excellent alkali resistance, smooth & matt finish, applies flows out evenly.



AMRÈLLA[®] Pink Wood Primer

BSC Pink wood primer is an oil-based wood primer, which is primarily used to protect all exterior timber surfaces. This product has excellent filling and sealing properties. It is normally used in conjunction with an undercoat and the appropriate finish/coats of paint. It offers good adhesion properties, Excellent hiding power, easy application with brush or roller for both interior & exterior.

AMRÈLLA[®] Red Oxide Primer

BSC Red oxide primer is a high quality, rust resistant primer ideal for use on ferrous and steel surfaces. It offers anti corrosion, excellent adhesion smooth, high bonding film, easy to cover, good opacity and spreading power and quick drying.



DISTEMPER COLLECTIONS

4001

Acrylic Washable Distemper

BSC 4001 acrylic distemper is water-based interior wall paint and gives walls a delightful attractive and matt finish that lasts for ages. A time-tested formulation with acrylic copolymer binder its special formulation ensures shade retention for a long and its fast drying property facilitates quicker completion of painting jobs. BSC 4001 acrylic distemper with better durability is one of the best performing distemper made by BSC Paints.



DELTA

Acrylic Washable Distemper

BSC Delta acrylic distemper is water based interior wall paint. It is a value for money brand that makes it possible for consumers to have beautiful walls at affordable rates. Being an acrylic finish, it offers a smooth finish. The shades retain their brightness for a longer time.

Putty : Polymer based white cement based putty (for both int. & ext.)

BSC Cement Putty for Interior & Exterior

QUALITY GUARANTEED

BSC Cement putty is a polymer and white/grey cement based premium wall putty mainly used for repairing, smoothening and leveling of walls, ceilings, floors etc. It has good adhesion, water resistance, does not crack and is compatible with all types of paints. It provides good opacity: facilitating more coverage to the paint.



BSC Acrylic Putty

BSC paint is one of the most acknowledged manufacturers and exporters of acrylic wall putty. It is highly resistance to water and moisture, ideal for filling and leveling compound formulated on acrylic co polymer. It is extremely suitable for interior surfaces.

Features:

- Easily Soluble in Water
- Easy to Apply
- Superior Quality
- Excellent Finishing
- Good Wash Ability
- Competitive Price



RainGaurd (Water Repellent)

It is a fiber reinforced elastomeric liquid applied water proofing membrane. It is formulated with select blastomeric and resilient acrylic polymers and reinforcing polyester fibers. Upon curing, in forms a thick, seamless, durable membrane thus offering ultimate waterproofing.

Special Coatings



BSC Bio-Wash (Pre-Treatment Coat)

It is water based acrylic coating for application on surfaces before painting to reduce and prevent growth of fungi and algae on surfaces. It's unique film-forming property retains the preservatives much longer for protection against bio attacks due to harsh weather conditions, there by enhancing the performance of the expensive topcoat material. It resists formation of black spots on the surface.



BSC paints®

ENAMEL COLLECTIONS



AMRELLA™ Synthetic Enamel

BSC Amrella is premium quality high gloss enamel that provides excellent weather resistance. It is especially formulated to give a tough and fungus free finishes with excellent gloss and color retention. BSC Amrella enamel is widely used on interior and exterior building surfaces made of wood, metal and masonry.



AMRELLA™ Lustre Finish Synthetic Enamel

BSC Lustre finish is recommended for int. use and can be used on plastered walls or wooden surfaces. It is a special enamel paint that imparts a hard film and if touched up with rollers while wet, offers a pearl-like lustre finish.

BSC paints offers high quality industrial paints offering smooth coating to agriculture equipments, machinery, flange and valve. Application: Agriculture equipments, machinery parts, submersible/electric motor, flange foot valve and diesels engine etc.

Hammertone Enamel

Quick drying multi-purpose hard wearing enamel with highly chemical resistant properties. Can be applied directly to decrease rust free metal

APPLICATION

For metal surface ensure that the surface to be coated free of oil. Dir and loose material. Wire brush or sand down previously rusted surfaces to metal. Apply by spray gun in a controlled wind free environment.

ADVANTAGES

- Quick Drying
- Highly Chemical Resistant Properties
- Only available in silver, light green and light blue
- Hard Wearing
- Self-priming on metal surfaces

Furniture Enamel

Used to paint furniture these paints not only enhance the beauty of furniture items, but also protect them from getting corroded or damaged. These paints are available in glossy as well as matte finishes as per the preference of the clients based on their requirements.

Features:

- Rust-Resistant
- Long Lasting
- Perfect Gloss
- Aesthetically appealing
- Fine Finish



Thinner

We offer superior thinners especially developed to provide effective usage as thinning agents and cleaning agents for a wide range of industrial applications.

- Water Base Thinner (Acrylic Paint Diluter)
- Reducer (Synthetic Paint Diluter)



for your home



TEXTURE FINISHES

Rustic

BSC Rustic is a most durable weather resistant finish with high abrasion resistance. Available in wide range of pigmented/ non-pigmented natural colours. It is highly in demand due to reliability & high performance acrylic resins.





Roller Coat / Super Fine

BSC ROLLER coat is said to be the most widely used texture coating for outdoor and inside. This coat is a water-repellent coating that offers wonderful confrontation and made up of special quartz & calcite.

Roller Coating have following features:-

- 1. It is odorless.
- 2. Non-Flammable
- 3. Environmentally Friendly.
- 4. Outstanding water resistance.
- 5. High Performance.
- 6. Excellent Product



Spray Coat


BSC Paints is the best manufacturer for spray coat. Spray Coating have the excellent feature for providing a flat coat textures. This is available in different combinations of colours like single, double and multi colours. Nowadays, spray coating is used in every house to make it different from other.

Granules

BSC Granules have the quality to control the weather, fungus, Water resistant. Granules coating is used inside and outside the building of all types. It is available in wide range of shades.

Multi Fancy

BSC Multi fancy is spray applied finish non-breakable with artificial fibers. The three dimensional effects and the attractiveness of the textures differentiate. Multi fancy from the other products.



Dholpur

'The Dholpur Granite'. Its an elegance of granite spread by trowel. Dholpur looks like short blasted Dholpur Natural Stone with an ease to take on any shape. It's a strong & durable finish and an economical alternative of expensive Dholpur Natural Stone. It is extremely suitable for interior and exterior.





BSC paints®

introducing INDUSTRIAL COATINGS



TSA Coating

Used as steel work for its excellent chemical resistance and weathering properties. Steel Cupboards, Bicycles, Wheels & Rims, Hinges, E-Rickshaws.

TSA clear is based on acrylic - amino system. It is a premium quality product designed economically to impart hard, durable & excellent protection to metal surface & good aesthetics look.

- Good weathering resistance • Excellent water resistance
- Chemical resistance • Excellent adhesion, hardness & abrasion resistant



Catalyzed Lacquer

Application areas are door handles, belt buckles, plated handicraft items and polished metal components. It can be applied by electrostatic spray.

Catalyzed lacquer : this product is hybrid chemistry 2k system and need baking @120deg/30mins. This product has excellent finished in transparent, frost and solid colors.



HPC Lacquer Clear

Used as possibilities on glass beads, iron structures, fancy lights for interior purpose only and also apply on silver nitrate coating. BSC solvents dyes can be mixed to get desired colour and effects.

HPC Clear Lacquer – this is epoxy based 2 k clear lacquer, air drying in nature. It has good adhesion on direct metal, plated items and glass substrates.

Lico Lacquer

Application areas are Liquor & Perfume bottles . It can be applied by electrostatic spray.

Lico lacquer : This product is hybrid chemistry 1k system and need baking @180deg/10mins. This product has excellent finished in transparent, frost and solid colours. Mostly for Industrial application.





PU

SUPER LUXURY & AUTOMOTIVE ENAMEL

Bsc Paints Super Luxury Coating PU interior & Exterior is acrylic based coating, which offers excellent stain resistance, better hardness and long-lasting durability. It also has a gloss and matte finish for multiple surfaces. It's tough film ensures no scratches and stains.

- TOUCH FILM
- CRACK RESISTANT
- NON YELLOWING
- ANTI FUNGAL



BSC FAST DRYING ENAMEL

BSC Fast Drying Synthetic Paint is a fast-drying, alkyd-based synthetic paint of high quality. It is particularly recommended for use where high-quality finishes are required with the paint having excellent adhesion to the surface applied, and where quick drying is suitable. It can be used on machinery, truck bodies (as suitable substitute to car paints) and for both internal and external wood and metal finishes.



BSC NC ENAMEL

BSC Nitrocellulose paint is a combination of rich solvents which helps in thinning the paints to desired viscosity. It also accelerates the flow and smoothen the film. It protects the paint from getting decayed. It has excellent compatibility with Nitrocellulose Lacquer and all other NC base items.

BSC GLASS COAT

This product is recommended as coating for glass substrate for application on perfume bottles, pharm bottles and many other glass articles. It can also be used for some special plated substrates directly. This product is recommended for glass and plated substrate. This is a two component product. Ensure recommended mixing proportions of base, hardener and thinner and apply within the specified pot life. Film properties to be checked after maturity of film varying from 3-7 days



BSC STOVING ENAMEL

It is a premium stoving Enamel Paints based on thermosetting resins and that cure on application of heat @ at 120 deg c for 30 minutes stoving schedule. Available in different shades as per shade card , It has good flexibility and adhesion ,fair gloss and chemical resistance.



BSC paints[®]

introducing CONCRETE FINISH



CONCRETE FINISH

The grey concrete specially for exterior is next gen texture. When you think grey. The very first you imagine concrete. BSC PAINT Concrete finish is very luxury texture product that give you actual decent concrete grey look.

BSC PAINT Concrete finish offer you all the look feel and style of authentic concrete without the hassle cost or a difficult installation process.



METALLIC PEARL: PREMIUM LUXURY EMULSION

BSC Metallic is luxurious Premium Metallic Emulsion paint for interior & exterior surfaces. It's unique formula provides special features like anti-stain, anti-fungal, increased wash ability, durability and pearl like elegant smoothness. Magic Coat: It is kind of non-metallic. It acts as Pg05. You can directly put stainers and use it. It also delays wetting for metallic pearls. Clear Coat: TC 100: Glitter Silica coat. /TC200: Silicon Coat/TC500: Pure Silicon coat.



GOLD SILVER COPPER




BSC WATERPROOFING SOLUTIONS

Bsc Paints water proofing is based on modified styrene butadiene latex supplied as a ready to use bonding agent in liquid consistency. It is used for repair of spalled concrete floors, columns, beams, chajas, slabs. Waterproofing of toilets & bathrooms, small terraces etc. It bonds strongly to old & new concrete and to plasters. It reduces shrinkage, prevents cracking, dust pick up improves abrasion resistance.






OUR **SIGNATURE** SPEAKS VOLUME ABOUT OUR EXISTENCE...



BSC paints

textured Paints

COLORS AND DESIGN



*Nayi Duniya
Naye Rang*





BSC paints



TEXTURE PAINT **RUSTIC**

Create a stylish impression with luxurious matt textures and rich colours.



BSC paints

TEXTURE PAINT **SUPERFINE**

Create quiet luxury with glistening textures that shimmer and shine.



BSCpaints



TEXTURE PAINT **PEARL**

Create subtle glamour with luminous textures enveloped in a pearlescent glow.





BSCpaints

TEXTURE PAINT **BSC DUNE**

The Dune effect has a slanted, gentle texture. As the name suggests, it is inspired by tropical rain.






BSCpaints

TEXTURE PAINT MULTI FANCY

Offered products are extremely employed by patrons for longer life and top quality. These are made at eco-friendly and advanced technology based unit.






BSC paints

TEXTURE PAINT STUCCO

Create finishes inspired by marble and other stone surfaces. It is a lime based plaster with a high sheen and smooth finish.





BSC paints



TEXTURE PAINT
DECOPIA

Pick from a large variety of textures available for different conditions and give your wall the perfect look.



BSC paints



TEXTURED PAINT SERIES

Create special textured walls with the Textured Paint series - an opaque wall finish, featuring 4 unique special effects.





BSC paints

INTRODUCING

CONCRETE
FINISH



www.bscpaints.com



Concrete For Exterior

The grey concrete specially for exterior is next gen texture. When you think grey. The very first you imagine concrete. BSC PAINT Concrete is very luxury texture product that give you actual decent concrete grey look.

BSC PAINT Concrete offer you all the look feel and style of authentic concrete without the hassle cost or a difficult installation process. Each urban concrete panel has been formed from a real concrete mold and them is hand painted to match the authentic look of poured concrete walls.



www.bscpaints.com



Concrete For Interior

The high class texture product made with some natural minerals & some chemicals with high strength destines.

Strength in concrete is too high level on our product it with our special product , protect coat & concrete material mixed with fiber. That make it crack proof.



www.bs paints.com





Concrete Finish

| MID GREY

The BSC decorative mid grey concrete is created by removing the surface fines from the concrete resulting in the internal aggregates being exposed highlighting the natural elements of the stone. BSC concrete finish is ideal for use on outdoor areas, the more heavily exposed finish is perfect for driveways or areas requiring more grip.

| LIGHT GREY

Light grey Concrete finish makes a bold new statement. Its unfinished earthy texture lends an industrial edge to the spaces. These finishes are available in a variety of hues & effects, and can be used either as an accent or on all walls in the room.

| DARK GREY

BSC Paints dark grey concrete finish can replace conventional horizontal concrete with finishes that replicate the beauty of natural stone, rock, ceramic, bricks and wooden planks - at reduced cost in comparison to the original products. In addition to cost saving, BSC Paints dark grey concrete resists all atmospheric agents and temperature changes, does not need any particular maintenance and is easy to keep clean.

| WHITE GREY

White concrete finish will make a visual impact in terms of design. It is also a very responsive form of concrete in terms of further decoration and finishing. Staining and coloring a white cement mix provides a brighter appearance. White concrete is also very reflective, which gives it a warmth and shimmer when it is sunlight.



Brighter Thinking
Better Painting



Plenty of possibilities

We proudly present our concrete inspired universal porcelain tiles. We put at your disposal nine collections which indulge us with a wide range of colours, variety of formats and different types of finishes.

The large format tiles available in this collection will form the background for modern arrangements and classic interiors. If we decide to install the available tiles, we will create a decorative element for our design. In both cases, the collections will indulge with their matte and lappato finish. Also noteworthy are step treads and baseboards which will complement the design of internal and external stairs.

We believe that our collections will help you make your dreams of a perfect interior come true.



BSC paints



GLASS LACQUER PAINTS

*Nayi Duniya*TM
Naye Rang



Glass Lacquer Paints from BSC paints

One of the latest innovations at BSC paints is an exquisite, attractive range of Glass fashions. This range includes:

- 1. Transparent / Opaque colours
- 2. Translucent Metallics
- 3. Special Effects – Marble, Splatter and Granite
- 4. Frosted Finishes
- 5. Customizable Stencil Designs



UTILITY

Using coloured glass has always been a decor must-do, be it the Church enclaves or even in classics like in Devdas, where the idea was extended to Art Deco elements - Lamp Shades, Vases, Planters, Murals, Glass Separators and utility areas like Glass Basins, Table Tops, Counter-tops, Ceilings, Railings, Wall Hangings, Kitchen Cabinets, Furniture and Banisters.



Splatter Granite Effect



Transparent Colour Combinations



*Excellent
Solutions
Infinite
Possibilities*

Frosted & Stencils



Glass possesses a number of unique properties, especially the ability to create different optical effects. It has always been a subject of expert's interest in the field of construction, interior decoration, furniture and more. With the global advancements in technology, Glass Coatings are the latest fashion trend even though the technique is available with a few select companies in India.



BSC paints

Recommended use

This product is recommended as coating for glass substrate for application on perfume bottles, pharma bottles and many other glass articles. It can also be used for some special plated substrates directly.

Application guidelines

This product is recommended for glass and plated substrate. Glass substrate must be free from dust grease etc. and should be cleaned with solvent. Nickel and gold plated substrate can be used after ultrasonic cleaning. It can also be used over nickel and GI substrate after ultrasonic cleaning. This is a two-component product. Ensure recommended mixing proportions of Base, Hardener and Thinner and apply within the specified pot life. Film properties to be checked after maturity of film varying from 3-7 days.

GLASS COATING CLEAR COAT



IN-CAN PROPERTIES

Viscosity @ 30°C	50 ± 5 sec. FCB4 cup	Specific gravity	0.97 ± 0.03
Non - volatile matter	42 ± 2%	Resistivity	N.A.
Chemical Composition	PU	Shelf life @ 30°C	One year in a tightly closed container

FILM PROPERTIES

Gloss @ 60°	95 ± 5
Scratch hardness	2 kg
Direct impact resistance	63 cm
Acetone double rub	50 Times
Alkali resistance	24 hrs
Grease resistance	24 hrs
Water immersion	24 hrs
Adhesion	0/25
Flexibility	6 mm
Xylene double rub	50 times
Acid resistance	24 hrs
Lubricating oil	24 hrs
Humidity resistance	240 hrs
Q-UV Weatherometer (ASTM G - 154)	700 hrs

APPLICATION PROPERTIES

Mixing ratio	4:1	Recommended thinner	Glass Coating PU Thinner
Thinner intake	20 - 25% (v/v)	Spray viscosity 30°C	18 + 2 sec, FCB4 cup
Pot life @ 25°C	>3 hrs	Drying	
Dry film thickness	25 - 35 micron	Surface dry	20 - 25 min
Coverage (on non-absorbent surface)	12 to 16 sq. m	Tack free dry	3 - 4 hrs
[Theoretical @ 25 to 35 micron per coat/Lt.]		Hard dry	16 hrs
		or	
		Flash off	10 min
		Forced drying	80°/ 30 min

Packs available 1lt, 4lt and 20lt

www.bscpaints.com



BSC paints

Recommended use

This product is recommended as coating for glass substrate for application on perfume bottles, pharma bottles and many other glass articles. It can also be used for some special plated substrates directly.

Application guidelines

This product is recommended for glass and plated substrate. Glass substrate must be free from dust grease etc. and should be cleaned with solvent. Nickel and gold plated substrate can be used after ultrasonic cleaning. It can also be used over nickel and GI substrate after ultrasonic cleaning. This is a two-component product. Ensure recommended mixing proportions of Base, Hardener and Thinner and apply within the specified pot life. Film properties to be checked after maturity of film varying from 3-7 days.

GLASS COATING ALL COLOURS



IN-CAN PROPERTIES

Viscosity @ 30°C	50 ± 5 sec. FCB4 cup	Specific gravity	1.00 ± 0.03
Non - volatile matter	46 ± 2%	Resistivity	N.A.
Chemical composition	PU	Shelf life @ 30°C	One year in a tightly closed container

FILM PROPERTIES

Gloss @ 60°	95 ± 5
Scratch hardness	2 kg
Direct impact resistance	63 cm
Acetone double rub	50 Times
Alkali resistance	24 hrs
Grease resistance	24 hrs
Water immersion	24 hrs
Adhesion	0/25
Flexibility	6 mm
Xylene double rub	50 times
Acid resistance	24 hrs
Lubricating oil	24 hrs
Humidity resistance	240 hrs
Q-UV Weatherometer [ASTM G - 154]	700 hrs

APPLICATION PROPERTIES

Mixing ratio	4:1	Recommended thinner	Glass Coating PU Thinner
Thinner intake	25 - 30% (v/v)	Spray viscosity 30°C	18 ± 2 sec, FCB4 cup
Pot life @ 25°C	>3 hrs	Drying	
Dry film thickness	20 - 25 micron	Surface dry	20 - 25 min
Coverage (on non-absorbent surface)	16 to 24 sq. m	Tack free dry	3 - 4 hrs
(Theoretical @ 15 to 25 micron per coat/Lt)		Hard dry	16 hrs
		or	
		Flash off	10 min
		Forced drying	80°/ 30 min

Packs available 1lt, 4lt and 20lt

www.bscpaints.com



BSC paints



Recommended use

This product is recommended as coating for glass substrate for application on perfume bottles, pharma bottles and many other glass articles. It can also be used for some special plated substrates directly.

Application guidelines

This product is recommended for glass and plated substrate. Glass substrate must be free from dust grease etc. and should be cleaned with solvent. Nickel and gold plated substrate can be used after ultrasonic cleaning. It can also be used over nickel and GI substrate after ultrasonic cleaning. This is a two-component product. Ensure recommended mixing proportions of Base, Hardener and Thinner and apply within the specified pot life. Film properties to be checked after maturity of film varying from 3-7 days.

GLASS COATING CRACKLE FINISH



IN-CAN PROPERTIES

Viscosity @ 30°C	50 ± 5 sec. FCB4 cup	Specific gravity	0.98 ± 0.03
Non - volatile matter	38 ± 2%	Resistivity	N.A.
Chemical composition	PU	Shelf life @ 30°C	One year in a tightly closed container

APPLICATION PROPERTIES

Mixing ratio	4:1	Recommended thinner	Glass Coating PU Thinner
Thinner intake	25 - 35% (v/v)	Spray viscosity 30°C	18 + 2 sec, FCB4 cup
Pot life @ 25°C	>3 hrs	Drying	
Dry film thickness	15 - 25 micron	Surface dry	20 hrs
Coverage (on non-absorbent surface)	12 to 21 sq. m	Tack free dry	3 hrs
(Theoretical @ 15 to 25 micron per coat/Lt)		Hard dry	16 hrs
		or	
		Flash off	10 min
		Forced drying	80°/ 30 min

FILM PROPERTIES

Gloss @ 60°	95 ± 5
Scratch hardness	2 kg
Direct impact resistance	63 cm
Acetone double rub	50 Times
Alkali resistance	24 hrs
Grease resistance	24 hrs
Water immersion	24 hrs
Adhesion	0/25
Flexibility	6 mm
Xylene double rub	50 times
Acid resistance	24 hrs
Lubricating oil	24 hrs
Humidity resistance	240 hrs
Q-UV Weatherometer (ASTM G - 154)	700 hrs

Packs available 1lt, 4lt and 20lt

www.bscpaints.com

BSC paints



Top Coat for
Wood | Metal | Walls



*Nayi Duniya
Naye Rang*

INDIA'S MOST
TRUSTED PAINT HAS
A NEW LOOK



BSC paints

Amrella Synthetic Enamel Paint

Bsc Paints Amrella Synthetic Enamel imparts a shiny new look to surfaces painted with this finish. It forms a tough film that is highly resistant to household stains. It thereby serves as a protective armour around the painted surface.



 SOLVENT BASED

Hardwearing and weather resistant.

No odour and quick drying.

Excellent coverage.

Very good levelling and flow.

Easy to use.



coverage

interior in 1 layer drying time

PRODUCT BENEFITS

High Gloss Finish

Amrella Synthetic Enamel gives a mirror like gloss for your doors, windows, grills & gates.

Stain Gaurd

Amrella Synthetic Enamel is a highly washable paint, thus you can wipe off most common household stains easily.

Tough and Durable

The oil based film of Amrella Synthetic Enamel makes it one of the toughest & most durable paints which forms a protective armour around surfaces.

PRODUCT FEATURES

WASHABILITY



FINISH



Refer to sheen levels in technical details

COLOURS AVAILABLE

1132



*Currently available in 1737 shades as per the Colourworld Fandeck



Amrella Premium Primer Paint

Bsc Paints Amreilla Premium Primer is suitable for use as a primer for masonry top coats like distemper, emulsion, luster and matt wall finishes. It helps in providing a suitable surface for application of subsequent coats of putty and finish paint.



SOLVENT BASED

- Hardwearing and weather resistant.
- No odour and quick drying.
- Excellent coverage.
- Very good levelling and flow.
- Easy to use.



interior coverage 10 m²/l 5 h 23°C drying me

PRODUCT BENEFITS

Bsc Paints Amrella Premium Primer sets fast, has good sealing properties, good resistance to wall alkalinity, moisture and fungus.

PRODUCT FEATURES

COLOURS AVAILABLE

- Surfacer White Primer
- Pink Wood Primer
- Red Oxide Primer



COVERAGE

On smooth masonry surface by brushing



1 COAT

130 - 160 sq.ft/ltr

DRYING TIME TO RECOAT



6-8 HOURS



BSC paints



*Nayi Duniya
Naye Rang*



INDIA'S MOST TRUSTED PAINT HAS A NEW LOOK

MECHANICAL STRENGTH

CRACK BRIDGING

SURFACE HEAT REDUCTION





BSC RX 746 WATER PROOFING URP

Bsc Paints Rx746 WaterProofing URP is based on modified styrene butadiene latex supplied as a ready to use bonding agent in liquid consistency. It is used for repair of spelled concrete - floors, columns, beams, chajas, slabs. Waterproofing of toilets & bathrooms, small terraces etc. It bonds strongly to old & new concrete and to plasters. It reduces shrinkage, prevents cracking, dust pick up improves abrasion resistance.

Benefits

- “ “ Waterproofs concrete during the construction stage.
- “ “ Improves workability.
- “ “ Avoids cracking.
- “ “ Protect concrete from corrosion.
- “ “ LW+ should be used in concrete, plaster and mortar in all the areas of house.
- “ “ Mix 200 ml of LW+ with every 50 kg bag of cement.



Consumption of BSC RX 746 WATER PROOFING URP in a 1000 sq.ft single storey house

Repair	Part of the House	Amount of Cement (50 kg bags)	Litres of WATERPROOFING URP
1	Foundation	35	7
2	Columns and Beams	100	20
3	Roof Slab and Screed	80	16
4	Lintel, Chhajja, Stairs and Water Tank	20	4
Plaster			
5	External Plaster	30	6
6	Internal Plaster	35	7
		300	60





BSC 101 LWB+

BSC 101 LWB PLUS is specially formulated integral liquid waterproofing compound composed of surfaer active plasticising agents, polymers & additives. It is used as an additive for cement concrete, mortar & plasters. It makes concrete cohesive and prevents segregation.

Benefits

- “ “ Waterproofs concrete during the construction stage.
- “ “ Improves workability.
- “ “ Avoids cracking.
- “ “ Protect concrete from corrosion.
- “ “ LW+ should be used in concrete, plaster and mortar in all the areas of house.
- “ “ Mix 200 ml of LW+ with every 50 kg bag of cement.



Consumption of BSC PAINT 101 LWB + in a 1000 sq.ft single storey house			
Repair	Part of the House	Amount of Cement (50 kg bags)	Litres of LWB+
1	Foundation	35	7
2	Columns and Beams	100	20
3	Roof Slab and Screed	80	16
4	Lintel, Chhajja, Stairs and Water Tank	20	4
Plaster			
5	External Plaster	30	6
6	Internal Plaster	35	7
		300	60





BSC RX 776 CONCRETE HARDENER

A clear fluorosilicate solution that case hardens poorly cured cement masonry structures by impregnating into its capillary spaces and then by chemically reacting with the free lime, it bonds and strengthens the crystalline structure.

- Easy to apply - sweep or brush on with a broom, mop or squeegee
- Permanently case hardens dusty or soft concrete or cement based structures by up to 300% of untreated concrete
- Dustproofs by bonding and strengthening the cement's crystalline structure
- Substantially increases the chemical and abrasion resistance
- Seals the structure against moisture penetration.



Consumption of RX 776 CONCRETE HARDENER in a 1000 sq.ft single storey house

Repair	Part of the House	Amount of Cement (50 kg bags)	Litres of CONCRETE HARDENER
1	Foundation	35	7
2	Columns and Beams	100	20
3	Roof Slab and Screed	80	16
4	Lintel, Chhajja, Stairs and Water Tank	20	4
Plaster			
5	External Plaster	30	6
6	Internal Plaster	35	7
		300	60





BSC DAMP PROOF

BSC PAINTS DAMP PROOF is a fiber reinforced elastomeric liquid applied water proofing membrane. It is formulated with select elastomeric and resilient acrylic polymers and reinforcing synthetic fibers. Upon curing, it forms a thick, seamless, durable membrane thus offering ultimate waterproofing.

Water proofing

Waterproofing protection of up to 7 bars of positive hydrostatic pressure

Crack bridging

Unmatched crack bridging ability due to elastomeric properties

Mechanical strength

Reinforced with synthetic fibers for superior abrasion resistance

Adhesion

Strong adhesion to masonry substrates

Surface temperature reduction

Provides surface temperature reduction up to 10°C.

This property is applicable for terraces and only for white shade

Use & maintenance

Single pack, easy to apply and simple re-coating

High sheen

High sheen, brilliant white colour and thick coat results in high levels of heat reflectance

Anti carbonation

Reduces carbon dioxide and chloride ion diffusion thus protecting re-bars against corrosion

Warranty

8 years Waterproofing warranty on Terraces and up to 8 Years on vertical surfaces


(*Warranty years on vertical surfaces will depend upon top coat used, please refer to warranty booklet for more details)



Consumption of BSC PAINT DAMP PROOF in a 1000 sq.ft single storey house

Repair	Part of the House	Amount of Cement (50 kg bags)	DAMP PROOF
1	Foundation	35	7
2	Columns and Beams	100	20
3	Roof Slab and Screed	80	16
4	Lintel, Chhajja, Stairs and Water Tank	20	4
Plaster			
5	External Plaster	30	6
6	Internal Plaster	35	7
		300	60





PU INTERIOR | PU EXTERIOR | MELAMINE | ZINC PRIMER | NC PAINT

BSC paints

GIVE NEW LIFE TO ALL WOOD SURFACES


THE BRAND OF INDIA
AN ISO 9001-2008 CO.



WOOD COATING PU INTERIOR

BSC paints

GIVE NEW LIFE TO ALL WOOD SURFACES



SUPER LUXURY WOOD COATING PU INTERIOR

BSC Paints Super Luxury Wood Coating PU Interior is acrylic based clear coating, which offers excellent stain resistance, better hardness and long-lasting durability. It also has a gloss and matte finish for multiple surfaces. It's tough film ensures no scratches and stains on the wood.

FEATURES

TOUGH FILM

It's superior film hardness making the product more durable.

NON YELLOWING

It's non yellowing feature making it retain gloss for longer.

CRACK RESISTANT

It has a strong yet flexible film, hence, it resists cracking even on curved surfaces.

ANTI FUNGAL

It offers high resistance to any algal or fungal attack

PRODUCT BENEFITS

DURABLE




VERY HIGH INTERIOR DURABILITY

FINISHES

MATT FINISH

GLOSS FINISH

AVAILABLE COLORS



AVAILABLE PACKS



DRY TIME



50 minutes

POST PAINTING CARE

For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.

If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.

Precautions need to be taken while spraying/ brushing, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.



WOOD COATING PU INTERIOR

BSC paints

GIVE NEW LIFE TO ALL WOOD SURFACES

HOW TO CHOOSE COLORS



HOW TO APPLY

PRE PAINTING STEPS

- SANDING:** Sand the wooden surface along the grains using sand paper no. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.
- INSULATING:** (Optional) Apply 1-2 coats of Insulator to insulate from oil & resin from the wood, also it reduces absorption of a paint material on Veneer.
- DENT FILLING:** If the surface has dents, apply WoodTech Filler with a putty knife over the dented area.
- STAINING:** To colour, apply Super Luxury Wood Coating Interiors by ragging or spraying. Allow to dry for 30 to 120 minutes.

PAINT APPLICATION PROCESS

CODE	MIXING RATION OF BASE	THINNER	DILUTION%	APPLICATION VISCOSITY	RECORDING PERIOD
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN (APPLY 3RD COAT IF REQUIRED BEFORE TOP COAT APPLICATION, SAND WITH SAND PAPER NO. 320 / 400 AND WIPE CLEAN)					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
(APPLY THIRD COAT IF REQUIRED AFTER SANDING WITH SAND PAPER NO. 320 / 400 AND WIPE CLEAN)					



WOOD COATING PU EXTERIOR

BSC paints

GIVE NEW LIFE TO ALL WOOD SURFACES

SUPER LUXURY WOOD COATING PU EXTERIOR

BSC Paints Super Luxury Wood Coating PU Exterior is acrylic based clear coating, which offers excellent stain resistance, better hardness and long-lasting durability. It also has a gloss and matte finish for multiple surfaces. It's tough film ensures no scratches and stains on the wood.



FEATURES

EXTERIOR DURABILITY

It has UV guards, which make the product an excellent product for exteriors

RESISTS CRACKING

It has a strong yet flexible film, hence, it resists cracking even on curved surfaces.

SUPERIOR RESISTANCE

for Exterior it has good scratch, stain and heat resistance.

HARDNESS

It has superior film hardness making the product more durable.

PRODUCT BENEFITS

DURABLE




HIGH EXTERIOR DURABILITY

FINISHES

MATT FINISH

GLOSS FINISH

AVAILABLE COLORS



AVAILABLE PACKS



DRY TIME



50
minutes

POST PAINTING CARE

For removing stains on tiles and metal surfaces, apply NC Thinner on the surface and wipe clean.

If stains are difficult to remove, scrapping can be done after applying NC thinner on the stained area.

Precautions need to be taken while spraying/ brushing, like masking of adjoining areas with suitable material, as the stains may be difficult to remove if present on wood or coated wooden and wall surfaces.



WOOD COATING PU EXTERIOR

BSC paints

GIVE NEW LIFE TO ALL WOOD SURFACES

HOW TO CHOOSE COLORS



HOW TO APPLY

PRE PAINTING STEPS

- SANDING:** Sand the wooden surface along the grains using sand paper no. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.
- INSULATING:** (Optional) Apply 1-2 coats of Insulator to insulate from oil & resin from the wood, also it reduces absorption of a paint material on Veneer.
- DENT FILLING:** If the surface has dents, apply WoodTech Filler with a putty knife over the dented area.
- STAINING:** To colour, apply Super Luxury Wood Coating Interiors by ragging or spraying. Allow to dry for 30 to 120 minutes.

PAINT APPLICATION PROCESS

CODE	MIXING RATION OF BASE	THINNER	DILUTION%	APPLICATION VISCOSITY	RECORDING PERIOD
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN (APPLY 3RD COAT IF REQUIRED BEFORE TOP COAT APPLICATION, SAND WITH SAND PAPER NO. 320 / 400 AND WIPE CLEAN)					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
SAND THE SURFACE WITH SAND PAPER 320 OR 400 AND WIPE CLEAN					
CODE	80:20	PU THINNER (1532/ 5442)	SPRAY 15 - 30	SPRAY 15 - 20 SECS	8 - 12 HOURS (SHOULD NOT EXCEED 72 HOURS)
(APPLY THIRD COAT IF REQUIRED AFTER SANDING WITH SAND PAPER NO. 320 / 400 AND WIPE CLEAN)					



BSC paints

Typical Uses

Used as steel work for its excellent chemical resistance and weathering properties. Steel Cupboards, Bicycles, Wheels & Rims, Hinges, E-Rickshaws.

DESCRIPTION

TSA clear Is based on acrylic - amino system. It is a premium quality product designed economically to impart hard, durable & excellent protection to metal surface & good aesthetics look.

- Good weathering resistance
- Excellent water resistance
- Chemical resistance
- Excellent adhesion, hardness & abrasion resistant

TSA COATING

THERMAL SPRAY ALUMINIUM COATING
ALL COLOURS



TECHNICAL DATA

- COLOR : ALL COLOUR
- COMPONENTS : Single
- FINISH : High - Gloss
- CURING MECHANISM : Stoving
- VISCOSITY : 75 seconds (Acrylic) (Ford B4)
- SPECIFIC GRAVITY : Approx. 1.00 + 0.05
- VOLUME OF SOLIDS : 40% approx.
- THINNER : BSC Stoving Thinner
- MIXING RATIO : 10-20% (Thinner)
- SPRAY VISCOSITY : 13 seconds (Ford B4)
- RECOMMENDED : 25-30um THICKNESS PER COAT
- THEORETICAL COVERAGE : 15m²/L (25um DFT)
- DRYING TIME : 120°C-130°C for 30 minutes
150°C-160°C for 20 minutes.
- SHELF LIFE : 6 Months (Unopened Recommended storage conditions)

SURFACE PREPERATION

- Use mechanical blasting or electrical sanding. To remove any coated material or oxide layers on the surface.
- Remove any dust, oil and other foreign contaminants that may affect adhesion properties by hand or power tools.
- For aluminium & galvanized steel use appropriate surface preparation.

APPLICATION INSTRUCTIONS

- Mix the contents in the container thoroughly before use.
- Adjust the viscosity of the paint with recommended thinner to the required viscosity.
- Allow 5 minutes flash off time between subsequent coatings.

Packs available 1lt, 4lt and 20lt

www.bscpaints.com



Typical Uses

Application areas are door handles, belt buckles, plated handicraft items and polished metal components. It can be applied by electrostatic spray.

DESCRIPTION

Catalyzed lacquer : this product is hybrid chemistry 2k system and need baking @120deg/30mins. This product has excellent finished in transparent, frost and solid colors.

CATALYZED LACQUER (CL.CO) ALL COLOURS



TECHNICAL DATA

- COLOR : ALL COLOR
- COMPONENTS : TWO PACK (9:1)
- FINISH : HIGH GLOSS
- CURING MECHANISM : STOVING
- VISCOSITY : 65 SEC (FORD B4)
- SPECIFIC GRAVITY : approx. 1.00 + 0.05
- VOLUME OF SOLIDS : 60% approx.
- THINNER : Catalyzed HPC Thinner
- MIXING RATIO : 50 – 60 % (Thinner)
- SPRAY VISCOSITY : 13 second (Ford B4)
- RECOMMENDED : 20 – 30um THICKNESS PER COAT
- THEORETICAL COVERAGE : 15m²/L (25um DFT)
- Acetone Rub :
- TYPE 1 - 8000 rub
- TYPE 2 - 2500 rub
- TYPE 3 - 1000 rub
- SHELF LIFE : 6 month (Unopened Recommended storage conditions)

APPLICATION INSTRUCTIONS

- Mix the contents in the container thoroughly before use.
- Adjust the viscosity of the paint with recommended thinner to the required viscosity.
- Allow 5 minutes flash off time between subsequent coatings.

Packs available 1lt, 4lt and 20lt

Toll free : 1800 - 11 - 4663

www.bscpaints.com



TYPICAL USES

Used as possibilities on glass beads, iron structures, fancy lights for interior purpose only and also apply on silver nitrate coating. BSC solvents dyes can be mixed to get desired colour and effects.

DESCRIPTION

HPC Clear Lacquer – this is epoxy based 2 k clear lacquer, air drying in nature. It has good adhesion on direct metal, plated items and glass substrates.

HPC LACQUER CLEAR ALL COLOR



TECHNICAL DATA

- COLOR : ALL COLOR
- COMPONENTS : TWO PACK (4:1)
- FINISH : HIGH GLOSS
- CURING MECHANISM : AIR DRYING
- VISCOSITY : 24 SEC (FORD B4)
- SPECIFIC GRAVITY : approx. 1.00 + 0.05
- VOLUME OF SOLIDS : 40% approx.
- THINNER : HPC Thinner
- MIXING RATIO : 30 – 40 % (Thinner)
- SPRAY VISCOSITY : 16 second (Ford B4)
- RECOMMENDED : 20 – 30um THICKNESS PER COAT
- THEORETICAL COVERAGE : 15m²/L (25um DFT)
- DRYING TIME : Surface Dry – 4 - 5 min, Tack free dry – 3hrs, Hard dry – 16hrs
- Force drying : 80°/ 30 min, Flash off – 10min.
- GLOSS @ 60° : 95 ± 5
- Scratch hardness : 2 kg
- Acetone double rub : 30 Times.
- SHELF LIFE : 6 month (Unopened Recommended storage conditions)

APPLICATION INSTRUCTIONS

- Mix the contents in the container thoroughly before use.
- Adjust the viscosity of the paint with recommended thinner to the required viscosity.
- Allow 5 minutes flash off time between subsequent coatings.



BSC paints



Typical Uses

Application areas are Liquor & Perfume bottles . It can be applied by electrostatic spray.

DESCRIPTION

Lico lacquer : This product is hybrid chemistry 1k system and need baking @180deg/10mins. This product has excellent finished in transparent, frost and solid colours. Mostly for Industrial application.

LICO LACQUER ALL COLOURS



TECHNICAL DATA

- COLOR : ALL COLOR
- COMPONENTS : Single
- FINISH : HIGH GLOSS
- CURING MECHANISM : STOVING
- VISCOSITY : 18 ± 2 (Acrylic) (ford B4)
- SPECIFIC GRAVITY : approx. $1.00 + 0.05$
- VOLUME OF SOLIDS : Approx 45 ± 2
- THINNER : BSC Lico Thinner
- MIXING RATIO : 5 – 10 % (Thinner)
- SPRAY VISCOSITY : 15 ± 2 second (Ford B4)
- RECOMMENDED : 20 – 30um THICKNESS PER COAT
- THEORETICAL COVERAGE : 15m²/L (25um DFT)
- DRYING TIME : 180^o - 190^o , 10 Minutes
- SHELF LIFE : 3 month (Unopened Recommended storage conditions)

APPLICATION INSTRUCTIONS

- Mix the contents in the container thoroughly before use.
- Adjust the viscosity of the paint with recommended thinner to the required viscosity.
- Allow 5 minutes flash off time between subsequent coatings.

Packs available 1lt, 4lt and 20lt

Toll free : 1800 - 11 - 4663

www.bscpaints.com